

TPSK

60 mm



Key features

- Cutter with integrated paper chute
- Extended temperature range for outdoor applications



CLAMSHELL™



MANUAL CUTTER



60 mm

CHARACTERISTICS	UNIT	TPSK
Printing speed (max)	mm/s	100
Printing width	mm	48
Resolution	dot/mm	8
Number of dots	dot	384
Columns	column	24 or 42
Character size	dot*dot	12*24 - 16*24
Resident code page	---	CP437, CP858, user fonts
Bar code type	---	Interleaved 2/5, UPC-A & UPC-E, JAN 8 (EAN) & JAN 13 (EAN), Code 39&128
Paper width	mm	60
Paper roll diameter	mm	102
Paper thickness	µm	60
Paper loading	---	Clamshell™
Operating voltage	VDC	12-24
Power consumption	W	55
Head pulse life	pulse	1*10 ⁸
Mechanical reliability	km	50
Dimensions (W*D*H)	mm	102*160*204
Weight	g	1700
Operating temperature	°C/F	-10 to 70 /14 to 158
Operating humidity	%RH	20 to 90 (non condensing)
Cutter	---	Auto cutter by pulling the ticket
Cutter life	cut	300K
Data buffer	Kbytes	1
Flash Memory extension	Mbytes	-
RAM Memory extension	Kbytes	-
Interface	---	RS232 or TTL
Driver	---	Windows™ 98/00/XP
CEM & Safety standards	---	UL60950, CSA 22.2-60950, CE Class B, FCC part 15 class A
Sensors	---	Paper low, paper out, door open & paper jam detector
Accessories	---	Power supply, communication cable